

## PRODUCT DATA SHEET

### Product view




### Product information

QR Code



Product group	Standard Coupling Type 2A
Item number	<b>CRA16164</b>
EAN-Code	4260182341643
Product name	Standard Coupling CTC 500 Type 2A Normallast / Hochlast

### Technical drawing



### Specification

A   Size range (mm)	485-500
B   Size range (mm)	-
L   Length (mm)	160
Pressure (bar)	0.6
Tightening torque (Nm)	13.0
Weight (kg)	3.45
Material	EPDM / V2A

### Product description

External flexible standard coupling designed to connect two vitrified clay pipes with the same dimensions (DN) as well as same materials and surface textures; shear band ensures joint integrity and pipe alignment under load; outside diameter differences with more than 12 mm have to be compensated with Crassus Bushes; in accordance with DIN EN 295-4; with acoustic decoupling; suitable for horizontal or vertical installation; suitable for flush-mounting and soil; UV-resistant material

### Certificates and approvals

MPA	-
CE	Yes
DIBT	-
SITAC	-
ETA	-

### Stable properties

Heat-resistant (Celsius Degree)	120
Cold-resistant (Celsius degree)	-40
UV-resistant	Yes
Ground-suited	Yes
Flush-mounting suited	Yes

