

PRODUCT DATA SHEET

Product view




Product information

QR Code



| | |
|---------------|--------------------------------|
| Product group | Floor Drain Frost-proof |
| Item number | CRA22802KG2 |
| EAN-Code | 4260431850193 |
| Product name | Floor Drain Frost-proof KG2000 |

Technical drawing



Specification

| | |
|--------------------------------|-----------|
| A Stainless steel grate (mm) | 150x150 |
| B Connection pipe ø (mm) | DN 110 |
| L Length (mm) | - |
| Pressure (bar) | 2.5 |
| Tightening torque (Nm) | - |
| Weight (kg) | 1 |
| Material | PP / EPDM |

Product description

For the installation in outdoor areas without traffic, drainage for gray water, drainage capacity: 1,67 l/s; water pressure-tight, circumferential Power-Profile; screwed stainless steel grate class K3 (maximum load up to 300 kg) 15x15 cm, frost-proof odor trap, sludge trap and protective cap (for construction period), height: floor drain about 110 mm, extension frame is infinitely adjustable 30 - 70 mm and twistable, connection to HT/KG-pipes DN 110 vertical

Certificates and approvals

| | |
|-------|-----|
| MPA | Yes |
| CE | - |
| DIBT | - |
| SITAC | - |
| ETA | - |

Stable properties

| | |
|---------------------------------|-----|
| Heat-resistant (Celsius Degree) | - |
| Cold-resistant (Celsius degree) | - |
| UV-resistant | Yes |
| Ground-suited | Yes |
| Flush-mounting suited | Yes |

