CRASSUS

be smart. be a Problemlöser.

Product datasheet as a PDF file

PRODUCT DATA SHEET

Product view

Product information

Designation	Press Seal Type DS-RT, DN 100mm for OD 0-75mm
Item number	**CRA21101V2A**

Product description

For the passage of ribbed or corrugated media pipes; for installation in core bores or casing pipes; resistant to pressurized and non-pressurized water; soft seal and central pressure plate for uniform pressure distribution with corrugated media pipes; damages and leakages are prevented; welded bolts for optimal stability and corrosion protection; UV and weather-resistant material.

Technical illustration



Dimensioning

A | Core drill hole	100 mm
B | Pipes / Cables ø	0-75 mm
L | Seal	40 mm

Specification

Pressure-tightness	1.0 bar / 14.5 PSI
Tightening torque	7.0 Nm
Weight	0.8 kg
Material	EPDM, Stainless steel (AISI 304)

Testing / Approval

MPA

Resistances

UV resistant	✔
Suitable for soil	✔
Flush-mounting suited	✔

Crassus GmbH & Co. KG
Josef-Orlopp-Straße 37
10365 Berlin, Germany
Local court Berlin
HRA 50944 B

Personally liable partner
Crassus Verwaltungs GmbH
Management Lars Baier
Local court Berlin
HRB 167557 B

Do you have any questions? USt-IdNr. DE300242912
Tel +49 30 3474 765-0
Fax +49 30 3474 765-20
Email info@crassus.de
Web www.crassus.de