



PRODUCT DATA SHEET

Product view






| Article group | Standard Coupling Type 2B FKM |
|---------------|-------------------------------|
| Item number | CRA14109FKM |
| EAN / GTIN | 4260431851831 |
| Designation | Standard Coupling CSC 125 FKM |

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning



| A Size range | 110-125 mm |
|----------------|------------|
| L Length | 120 mm |
| | |

Specification

| Pressure density | 2,5 bar |
|-----------------------------------|---------------------------------|
| Vacuum pressure density | -0,3 bar |
| High-pressure flushing resistance | 120 bar |
| Socket wrench insert | SW 8 mm |
| Tightening torque | 6,0 Nm |
| Weight | 0.9 kg |
| Material | FKM, Stainless steel (AISI 304) |
| | |



CE marking according to

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de

| Resistances | |
|-----------------------|--------|
| Heat resistant | 200 °C |
| Cold resistant | -25 °C |
| UV resistant | • |
| Suitable for soil | • |
| Flush-mounting suited | / |

ISO 1629, ASTM D 1418



Crassus GmbH & Co. KG

Josef-Orlopp-Straße 37 10365 Berlin, Germany