



# **PRODUCT DATA SHEET**

#### **Product view**





Article group	Standard Coupling Type 2B FKM
Item number	CRA16221FKM
EAN / GTIN	4260431851879
Designation	Standard Coupling CSC 275 FKM

#### **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

#### **Technical illustration**

### **Dimensioning**



L   Length	150 mm
A   Size range	250-275 mm

### **Specification**

Pressure density	2,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	10.0 Nm
Weight	1 kg
Material	FKM, Stainless steel (AISI 304)



# **CE** marking according to

Do you have any questions? USt-IdNr. DE300242912 Tel  $+49\,30\,3474\,765-0$  Fax  $+49\,30\,3474\,765-20$  Email info@crassus.de Web www.crassus.de

Resistances	
Heat resistant	200 °C
Cold resistant	-25 °C
UV resistant	•
Suitable for soil	•
Flush-mounting suited	<b>✓</b>

ISO 1629, ASTM D 1418

Crassus GmbH & Co. KG

Josef-Orlopp-Straße 37 10365 Berlin, Germany