



# **PRODUCT DATA SHEET**

#### **Product view**

#### **Product information**



Article group	Standard Coupling Type 2B FKM
Item number	CRA16222FKM
EAN / GTIN	4260431851664
Designation	Standard Coupling CSC 290 FKM

#### **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

#### **Technical illustration**

#### **Dimensioning**



A   Size range 26	55-290 mm
L   Length 15	50 mm

## Specification

•	
Pressure density	2,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	10.0 Nm
Weight	1.7 kg
Material	FKM, Stainless steel (AISI 304)



### **CE** marking

according to	ISO 1629, ASTM D 1418
Resistances	

Heat resistant	200 °C
Cold resistant	-25 °C
UV resistant	•
Suitable for soil	•
Flush-mounting suited	✓