



# **PRODUCT DATA SHEET**

#### **Product view**



#### **Product information**

Article group	Standard Coupling Type 2B XL
Item number	CRA16880
EAN / GTIN	4260431853897
Designation	Standard Coupling CSC XL 1505

## **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

## **Technical illustration**





## **Dimensioning**

Do you have any questions? USt-IdNr. DE300242912 Tel  $+49\,30\,3474\,765-0$  Fax  $+49\,30\,3474\,765-20$  Email info@crassus.de Web www.crassus.de

A   Size range	1490-1505 mm
L   Length	300 mm
Specification	
Pressure density	0.6 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 13 mm
Tightening torque	25 Nm
Weight	33.6 kg
Material	EPDM, Stainless steel (AISI 304)
CE marking	
according to	EN 681-1, EN 16397
Resistances	
Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	✓

