



PRODUCT DATA SHEET

Product view





Product information

| | |
|---------------|------------------------------|
| Article group | Standard Coupling Type 2B XL |
| Item number | CRA16936 |
| EAN / GTIN | 4260431853422 |
| Designation | Standard Coupling CSC XL 800 |

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration



Dimensioning

| | |
|----------------|------------|
| A Size range | 785-800 mm |
| L Length | 300 mm |

Specification

| | |
|-----------------------------------|----------------------------------|
| Pressure density | 1.5 bar |
| Vacuum pressure density | -0,3 bar |
| High-pressure flushing resistance | 120 bar |
| Socket wrench insert | SW 13 mm |
| Tightening torque | 20 Nm |
| Weight | 15.7 kg |
| Material | EPDM, Stainless steel (AISI 304) |

CE marking

| | |
|--------------|--------------------|
| according to | EN 681-1, EN 16397 |
|--------------|--------------------|

Resistances

| | |
|-----------------------|--------|
| Heat resistant | 120 °C |
| Cold resistant | -40 °C |
| UV resistant | ✓ |
| Suitable for soil | ✓ |
| Flush-mounting suited | ✓ |

