



## PRODUCT DATA SHEET

### Product view





### Product information

Article group	Standard Coupling Type 2B XL
Item number	<b>CRA16968</b>
EAN / GTIN	4260431853743
Designation	Standard Coupling CSC XL 1280

### Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

### Technical illustration



### Dimensioning

A   Size range	1265-1280 mm
L   Length	300 mm

### Specification

Pressure density	1.0 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 13 mm
Tightening torque	25 Nm
Weight	27.8 kg
Material	EPDM, Stainless steel (AISI 304)

### CE marking

according to	EN 681-1, EN 16397
--------------	--------------------

### Resistances

Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	✓

