



## **PRODUCT DATA SHEET**

#### **Product view**

#### **Product information**




Article group	Standard Coupling Type 2B
Item number	CRA14042
EAN / GTIN	4260182340424
Designation	Standard Coupling CSC 170

#### **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

#### **Technical illustration**

#### **Dimensioning**



A   Size range 150-	-170 mm
L   Length 120	mm

### **Specification**

-	
Pressure density	2,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	6,0 Nm
Weight	0.902 kg
Material	EPDM, Stainless steel (AISI 304)



# **CE marking** according to

Resistances	
Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	<b>✓</b>
Suitable for soil	✓
Flush-mounting suited	<b>✓</b>

EN 681-1, EN 16397