

be smart. be a Problemlöser.




PRODUCT DATA SHEET

Product view



Technical illustration





Product information

Article group	Standard Coupling Type 2B
Item number	CRA16787
EAN / GTIN	4260431852203
Designation	Standard Coupling CSC 755

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Dimensioning

A Size range	740-755 mm
L Length	190 mm
Specification	
Pressure density	1,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 13 mm
Tightening torque	20 Nm
Weight	8.5 kg
Material	EPDM, Stainless steel (AISI 304)
CE marking	
according to	EN 681-1, EN 16397
Resistances	
Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	<i>v</i>
Suitable for soil	<i>v</i>
Flush-mounting suited	<i>J</i>



Crassus GmbH & Co. KG Josef-Orlopp-Straße 37 10365 Berlin, Germany Local court Berlin HRA 50944 B

G Personally liable partner Crassus Verwaltungs GmbH Management Lars Baier Local court Berlin HRB 167557 B

Do you have any questions? USt-IdNr. DE300242912 Tel +49 30 3474 765-0 Fax +49 30 3474 765-20 Email info@crassus.de Web www.crassus.de