



# **PRODUCT DATA SHEET**

### **Product view**






| Article group | Standard Coupling Type 2B FKM |
|---------------|-------------------------------|
| Item number   | CRA14037FKM                   |
| EAN / GTIN    | 4260431851619                 |
| Designation   | Standard Coupling CSC 115 FKM |

### **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

### **Technical illustration**

### **Dimensioning**





## **Specification**

| Pressure density                  | 2,5 bar                         |
|-----------------------------------|---------------------------------|
| Vacuum pressure density           | -0,3 bar                        |
| High-pressure flushing resistance | 120 bar                         |
| Socket wrench insert              | SW 8 mm                         |
| Tightening torque                 | 6,0 Nm                          |
| Weight                            | 0.7 kg                          |
| Material                          | FKM, Stainless steel (AISI 304) |
|                                   |                                 |

# Commit

# **CE marking** according to

| Resistances           |          |
|-----------------------|----------|
| Heat resistant        | 200 °C   |
| Cold resistant        | -25 °C   |
| UV resistant          | •        |
| Suitable for soil     | •        |
| Flush-mounting suited | <b>✓</b> |

ISO 1629, ASTM D 1418

